


Wall Mount CO2 monitor

Specification

Display mode	LED display
Carbon Dioxide(CO2)	0~9999PPM
Accuracy	±50 ppm or ±5%(0~5000PPM)
Resolution	1PPM
Response time	10s
Repeatability	±20ppm
Formaldehyde	0~1000PPM
Accuracy	±5%
TVOC range	-10~70°C
Temperature Range	±0.5°C/±0.9°F
Temperature Accuracy	0-99.9%RH
Humidity Range	±3%RH(20%RH~80%RH)
Humidity Accuracy	adaptor(DC9v)
Power	0 to 50°C; 10%RH to 90%RH
Operating Environment	-20 to 60C; 10%RH to 75%RH
Sensor life	15 years in normal comm
Size	388×288×43mm
Wight	2420g



HT-2009



CO2 meter

Carbon dioxide meter is widely used in factory,workshop, green house,clean room,industry and agriculture,wine bar,hotel,hospital,shop market,airport,railway station, entertainment hall and moive theater etc.

Specification

Large LCD Display	Color display with backlight
Logger mode	key start/stop,Immediately,Schedule,Real-time&Roll-over
Carbon Dioxide(CO2)	
Range	0~9999PPM
Accuracy	±70ppm or ±3% rdg (0~5000PPM)
Response time	1s
Temperature Range	-10~70°C(14~158°F)
Resolution	0.1°C/°F
Accuracy	±0.3°C(10~50°C) ,others ±1.2°C
Humidity Range	0.1~99.9%RH
Resolution	0.1%
Accuracy	±3%(10~90%)
Logging Memory	12700
Operating Condition	0~50°C,0~85%RH (No Condensation)
Storage Condition	-20~60°C,0~99%RH (No Condensation)
Sensor life	15 years in normal comm
Storage temp	-20~60°C,0~90%RH (No Condensation)
Battery	3.7V rechargeable Li-ion polymer battery
Size	107×107×59mm



HT-501

LINE ID: @neonics



ติดต่อบริษัท นีโอนิกส์ จำกัด

Tel: 02-077-7602 หรือ 061-8268939

E-mail: sale@tools.in.th หรือ sale@neonics.co.th