

MOISTURE TESTER
MS6900 / MS6900A

ติดต่อบริษัท นีโอนิกส์ จำกัด
Tel: 02-077-7602 หรือ 061-8268939
E-mail: sale@neonics.co.th หรือ sale@tools.in.th




MS6900

DEPTH
0~50mm

RESOLUTION
0.1%, 0.1°C, 0.1°F
0.1%RH

°F/°C

MAX MIN



MS6900A

DEPTH
0~50mm

RESOLUTION
0.1%, 0.1°C, 0.1°F
0.1%RH

°F/°C

MAX MIN



| Specifications | | MS6900 |
|---------------------------------|---|-------------|
| Specifications | Range | Accuracy |
| Depth | | 0~50mm |
| Ambient TEMP | -10°C~50°C/14°F~122°F | ±0.2°C/±1°F |
| Electric Conductivity | 0.0~60.0% | ±1% |
| Humidity | 10~90% | ±5% |
| Features | | |
| MAX/MIN | | ● |
| Sampling Rate | Moisture and Humiture | ● |
| Unit Selection | %, WB, TD, °C, °F, %RH | ● |
| Display Backlight | | ● |
| Data Hold | | ● |
| LBD | Low Battery Display | ● |
| Materials Moisture Range | | |
| 1: (8.5~60%) | Beech, Spruce, Larch, Birch, Cherry, Walnut | |
| 2: (6.8~53.4%) | Oak, Cedar, Maple, Ash Tree, Pink Shower Tree, Tamarisk | |
| 3: (0.9~24.5%) | Smoothing Cement, Concrete | |
| 4: (0.0~12.2%) | Anhydrite Screed | |
| 5: (0.7~9.2%) | Cement Mortar | |
| 6: (0.5~11.1%) | Lime Mortar, Plaster | |
| 7: (0.0~17.8%) | Brick | |
| General | | |
| Power Supply | 2x1.5V AAA Batteries | |
| Product Size | 130mmx56mmx29mm/5.1"x2.2"x1.1" | |
| Product Weight | 120g/0.26lb | |
| Safety Rating | CE(EMC) RoHS | |

| Specifications | | MS6900A |
|---------------------------------|---|-------------|
| Specifications | Range | Accuracy |
| Depth | | 0~50mm |
| Ambient TEMP | -10°C~50°C/14°F~122°F | ±0.2°C/±1°F |
| Electric Conductivity | 0.0~60.0% | ±1% |
| Humidity | 10~90% | ±5% |
| Features | | |
| Auxiliary | Verification Test Points | ● |
| MAX/MIN | | ● |
| Sampling Rate | Moisture and Humiture | ● |
| Unit Selection | %, WB, TD, °C, °F, %RH | ● |
| Display Backlight | | ● |
| Data Hold | | ● |
| LBD | Low Battery Display | ● |
| Materials Moisture Range | | |
| 1: (8.5~60%) | Beech, Spruce, Larch, Birch, Cherry, Walnut | |
| 2: (6.8~53.4%) | Oak, Cedar, Maple, Ash Tree, Pink Shower Tree, Tamarisk | |
| 3: (0.9~24.5%) | Smoothing Cement, Concrete | |
| 4: (0.0~12.2%) | Anhydrite Screed | |
| 5: (0.7~9.2%) | Cement Mortar | |
| 6: (0.5~11.1%) | Lime Mortar, Plaster | |
| 7: (0.0~17.8%) | Brick | |
| General | | |
| Power Supply | 2x1.5V AAA Batteries | |
| Product Size | 130mmx56mmx29mm/5.1"x2.2"x1.1" | |
| Product Weight | 120g/0.26lb | |
| Safety Rating | CE(EMC) RoHS | |

COMBUSTIBLE GAS DETECTOR
MS6310



MS6310

RESOLUTION
50 ppm

ALARM
10%~40%

GAS LED

| Specifications | | MS6310 |
|---|--------------------------------|------------|
| Specifications | | |
| Resolution (methane) | | 50ppm |
| Alarm at Level | | 10%~40% |
| Warm Up Time | | 2 Minutes |
| Response time (40% LEL) | | <2 Seconds |
| Feature | | |
| Easy To Identify and Pinpoint Gas Leaks | | ● |
| Portable and High Sensitivity | | ● |
| Resume Original Measurement State after 7~10 minutes in Clean air | | ● |
| Gas Detected: Natural gas, Methane, Ethane, Propane, Butane, Acetone, Alcohol, Ammonia, Steam, Carbon Monoxide, Gasoline, Jet fuel, Hydrogen Solvents, Lacquer thinner, Naphtha | | ● |
| General | | |
| Power Supply | 4x1.5V AAA Batteries | |
| Product Size | 172mmx70mmx46mm/6.8"x2.8"x1.8" | |
| Product Weight | 354g/0.78lb | |
| Safety Rating | CE(EMC) RoHS | |

