

WALL-MOUNTED SOUND LEVEL METER



9.6" Standard Display

SW-525G



18" Large Display

SW-526A

SW-525A/SW-525B/SW-525G/SW-526A

ITEMS	SW-525A	SW-525B	SW-525G	SW-526A
Measuring Range	30.0~130.0dB			
Accuracy	±1.5dB (In Standard sound: 94dB@1KHz)			
Frequency range	31.5 Hz ~ 8.5 KHz			
Frequency weighting	A			
Response time	FAST			
Microphone	6mm Capacitance Microphone			
Display	3 digits display			
Resolution	0.1dB (30.0~99.9) 1dB (100~130)			
Alarm Reminder (sound + display)	√			
Alarm output	√			
Storage function	X	2 secs./time, can be stored for a year		X
Communication	X	connecting computer with USB cable		X
Power supply	DC5V 1A Micro USB Outlet	DC5V 1A Micro USB Outlet		5V 2A DC
Operating conditions	0 ~ 40°C, 10% ~ 80%RH			
Storage conditions	-10~60°C, 10% ~ 70%RH			
LED light color	Red	Red	Green	Red
Dimension	210*130*28mm	210*130*28mm	210*130*28mm	400*230*34.5mm
Weight	453g	453g	453g	1442g

Pictures only for reference, product in kind prevail.

PM2.5 DETECTOR

- PM2.5
- Temperature
- Humidity



SW-825

SW-825

ITEMS	SW-825
PM2.5 Measuring Range	0 ~ 500µg/m³
PM2.5 Single Response Time	<1s
PM2.5 Integrated Response Time	≤10s
PM2.5 Resolution Rate	1µg/m³
Particle count efficiency	50%@0.3µm 98%@≥0.5µm
Mass Concentration Consistency of Particulate Matter	±10%@100 ~ 500µg/m³, ±10µg/m³@0 ~ 100µg/m³
Temperature Measuring Range	-10.0°C ~ 50.0°C
Temperature Measuring Accuracy	±1.0°C
Humidity Measuring Range	0% ~ 99%RH
Humidity Measuring Accuracy	±10%RH
PM2.5 Sensor	Plantower Laser Particulate Matter Sensor
Battery Life for Once Charging	≥4.5hours
Auto Power off	30 minutes (The device cannot be power off automatically while charging time.)
Charging	DC 5V, 500mA, USB Connector
Battery	Li-ion 580mAh
Operating conditions	-10.0°C ~ 50.0°C, 0% ~ 99%RH
Net Weight	86g
Dimension	60x60x26mm

Pictures only for reference, product in kind prevail.



Activity Site



Classroom



Shopping Mall



Hospital



Office