



HT-801



## Bluetooth Temperature And Humidity Meter

Temperature and humidity meter is used for measuring the surroundings temperature and humidity so that we can know the environment conditions for production and storage.

### Specification

Humidity range	0~100%RH
Temperature range	-20°C~80°C(-4°F~176°F)
Dew point temperature	(-20°C~80°C/-4°F~176°F)
Wet Bulb temperature	0°C~80°C/32°F~176°F)
Humidity accuracy	±3%RH(25°C,20%~80%RH). ±2.5%RH(At other ranges)
Air temperature accuracy	±0.8°C/±0.9°F(25°C) ±0.8°C/±1.5°F(At other ranges)
Resolution	0.01%RH,0.01°C/0.01°F
Response time	10S
3 AAA batteries	
The device can with a small display, the APP of Android and IOS can monitoring data remotely (Bluetooth transmission)	
Can generate digital charts, trend graphs;	
Support to save / share data graphs .xls	
Support save / share trend graphs .jpg	
IOS8.3 / Android 4.3 above (bluetooth4.0)	

## Ultrasonic Distance Meterpower

It can be used for ultrasonic distance measuring,main apply to measure the distance of urban road plannig, construction site,industrial spot,etc.

### Specification

Power supply	9V
Unit of measurement	ft/m
Accuracy	0.5%±1Digits(2-60ft)
Working frequency	40KHz
Working temperature(Fahrenheit degree)	32-109.4°F
Range	2-60ft(0.55~18.288m)
Laser Diode Type	Red laser diode 650nm
Size	185×75×35mm 30s auto tum off
Weight	208g



HT-526

## Digital Tachometer

Commonly used in motor,electric fan,paper making,plastic, chemical fiber,washing machines and cars field.

### Specification

Measurement	Contact	1~19999
	Non-contact	1~19999
	999999counts	999999Counts
Display	Contact	
Target distance	Non-contact	50mm~600mm
Best Accuracy	0.02%±2dgt	
Auto power off	15s	
Max / min / road / M / min M / s feet / minute feet / sec / min		
Size	236×72×35mm	
Weight	218g	



HT-522



ติดต่อบริษัท นีโอนิกส์ จำกัด

Tel: 02-077-7602 หรือ 061-8268939

E-mail: sale@tools.in.th หรือ sale@neonics.co.th